

Little Mule®
MATERIALS HANDLING

Industrial trucks and elevating platforms



No. 4

**Yale Industrial
Products GmbH**

Contents

		Page
Hand pallet trucks		
Hand pallet truck	HU Profi	3
Hand pallet truck special	HU Special	4
Stainless steel hand pallet truck	HU PE	5
Scissor pallet trucks	HU HS 10 · HU ES 10	5
Special equipment		4
Hand pallet trucks with weighing system		
Hand pallet truck	HU PW	3
Stainless steel hand pallet truck	HU PWE	5
Pallet lift trucks • Order picking trucks		
Pallet lift truck	EGU EL	6
Pallet lift truck	EGU ES	6
Order picking truck	EKU EK	6
Drum lifter		
Drum lifter	FH 300	7
Manual drive stackers		
Manual drive stacker / Pallet lifter	HV TH	7
Manual drive stacker	HV TM	7
Electric pedestrian stackers		
Electric pedestrian stacker	EGV TG	8
Electric pedestrian stacker	EGV LE	8
Electric pedestrian stacker	EGV LV	9
Electric pedestrian stacker with initial lift	EGI LD	9
Electric pedestrian four-way stacker	EGY LW	10
Accessories		
Batteries		10
Battery charger		10
Attachments		10
Elevating platforms		
Scissor elevating platform	HF/S	11
Scissor elevating platform	HF/D	11
Elevating work bench	HT	11

Hand pallet truck Model HU Profi

for the professional transportation of palletised goods under demanding conditions

- Safety control handle with the functions: lifting - driving - lowering
- Finely adjustable lowering speed
- Low maintenance hydraulic with hard chromium plated piston and pressure relief valve
- Maintenance-free ball bearings (2 RS) DIN 625



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
HU Profi 25S (Single)	2,5 / 1.150	VG / PA Single	*254274
HU Profi 25S (Single)	2,5 / 1.150	VG / PUR Single	*254281
HU Profi 25S (Single)	2,5 / 1.150	PUR / PUR Single	*251877
HU Profi 25T (Tandem)	2,5 / 1.150	VG / PA Tandem	*253727
HU Profi 25T (Tandem)	2,5 / 1.150	VG / PUR Tandem	*253802
HU Profi 25T (Tandem)	2,5 / 1.150	PUR / PA Tandem	*251723
HU Profi 25T (Tandem)	2,5 / 1.150	PUR / PUR Tandem	*251747
HU Profi 30T (Tandem)	3,0 / 1.150	PUR / PA Tandem	*252188

Special equipment for pallet trucks
see page 4

Hand pallet truck with weighing system Model HU PW

robust construction of the basic unit and high quality electronics make demanding applications possible. Fitted with four load cells the hand pallet truck becomes a mobile weighing system.

- Tare, RS 232 interface, automatic return to zero
- Split-range weighing
- Smallest value 1 kg
- Pallet entry height just 85 mm
- LED display (83plus) with 6 characters, 20 mm high
- With counting and totalizer function
- PC configurable
- Easy calibration, accuracy $\pm 0,1\%$ of the end value
- Battery and charger are supplied with the truck



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
HU PW 20T - 83plus	2,0 / 1.140	PUR / PA Tandem	*252683
with printer: HU PW 20TR - 83plus	2,0 / 1.140	PUR / PA Tandem	*253130

Stainless steel version
see page 5

Optional extras:

HU PW with weighing range 2.500 kg (not for HU PWE 20T)

Change setting of partition

Higher accuracy $\pm 0,1\%$ of the measured value (Multi range scale)



LED display 83plus



Printer

Hand pallet trucks Model HU Special

Model HU PS

for professional work on lorries or ramps and for the transport of long and bulky loads

- fork lengths from 800 mm through 2.000 mm

Model HU PN

for the transport of particularly low pallets

- with flat forks, for 58 mm pallet entry height

Model HU PB

for the transport of small pallets

- outside fork distance 400 mm

Model HU TZ

for the transport of brickyard pallets

- outside fork distance 850 mm



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
HU PS 800S	2,5 / 800	PUR / PA Single	*252089
HU PS 800T	2,5 / 800	PUR / PA Tandem	*252096
HU PS 950S	2,5 / 950	PUR / PA Single	*252126
HU PS 950T	2,5 / 950	PUR / PA Tandem	*252133
HU PS 1350T	2,5 / 1.350	PUR / PA Tandem	*252201
HU PS 1500T	2,5 / 1.500	PUR / PA Tandem	*252218
HU PS 1800T	2,0 / 1.800	PUR / PA Tandem	*252225
HU PS 2000T	2,0 / 2.000	PUR / PA Tandem	*252232
HU PN 20T	2,0 / 1.150	VG / S Tandem	*250191
HU PB 20T	2,0 / 800	VG / PA Tandem	*250221
HU Profi 20 TZ	2,0 / 1.150	PUR / PUR Tandem	*253741

Pallet truck special equipment (Surcharge per truck)

Equipment	for model
Steering wheels PUR	all except HU Secure
Steering wheels VG	all except HU Secure
Steering wheels PA	all except HU Secure
Load rollers Single PUR	all
Load rollers Tandem PUR	all except HU PN
Quick lift	all except HU PN, HU Secure
Drive and parking brake*	all except HU HS, HU ES, HU PN
Steering wheels conductive	all except HU Secure
Steering + load wheels steel	all except HU PN, HU PV, HU Secure

* Driving brake up to 2,0 t; Parking brake up to 3,0 t, Tyres: PUR

Stainless steel hand pallet truck Model HU PE

for the professional transport of palletised goods in corrosive areas in the chemical and food processing industries.

- Polyurethane steering wheels and Polyamide load rollers offer greater resistance to aggressive chemicals
- Maintenance-free deep groove ball bearing
- Hydraulic unit zinc plated and blue chromated



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
HU PE 20T stainless steel	2,0 / 1.150	PUR / PA Tandem	*252966

Stainless steel cleansing agent, 500 ml
Stainless steel polish, 400 ml

*210157
*210164

Stainless steel hand pallet truck with weighing system Model HU PWE

for the professional transport and weighing of palletised goods in corrosive areas in the chemical and food processing industries.

- Features like HU PW (see page 3)
- Battery and charger are supplied with the truck



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
HU PWE 20T - 83plus	2,0 / 1.150	PUR / PA Tandem	*254175

Scissor pallet truck with manual/hydraulic lift Model HU HS 10

a combination of hand pallet truck and elevating platform for the transport and raising of palletised loads to various working heights in manufacturing, assembly and packing departments

- Overload protection by pressure relief valve
- Lowering speed can be finely metered for sensitive lowering of the load
- Safety supports guarantee sure standing when the forks are raised



Pallet truck special equipment
see page 4

Scissor pallet truck with electro/hydraulic lift Model HU ES 10

increases the usefulness of the HU HS 10 by saving operating time, for demanding applications with frequent lifting and lowering operations

- Battery and charger are delivered with the truck



Model	Capacity (t) / Fork length /-height (mm)	Tyres	EAN-No. 4025092*
HU HS 10-54	1,0 / 1.150 / max. 800	PUR / PUR Single	*250573
HU ES 10-54	1,0 / 1.150 / max. 800	VG / PUR Single	*250597

Standard outside fork width 540 mm; Optional fork width 680 mm on request.



Electric pallet lift truck Model EGU EL

ideal unit for working on ramps or taking along on a lorry

- Multi-functional control handle
- Fore part dimension 435 mm
- Impulse control for stepless regulation of travel speed
- Operating time according to battery capacity
- Battery and charger integrated

Model	Capacity (t) / Fork length / width (mm)	Tyres	EAN-No. 4025092*
Starter battery			
EGU EL 14-52/11	1,4 / 1.150 / 525	VG / PUR Single	*254427
EGU EL 14-52/11	1,4 / 1.150 / 525	VG / PUR Tandem	*254434
Traction battery			
EGU EL 14-52/11	1,4 / 1.150 / 525	VG / PUR Single	*254441
EGU EL 14-52/11	1,4 / 1.150 / 525	VG / PUR Tandem	*254458

Fork length 1.000 mm and fork width 680 mm on request

Electric pallet lift truck Model EGU ES

for high demands and quick turnaround in continuous applications, also suitable for loading/unloading of lorries and ramp work

- Spring-mounted central drive unit with 1,2 kW motor, optional: 1,7 kW
- Hoist motor 2,6 kW; pressure relief valve for safety
- Impulse control and multi-functional control handle
- Fork lengths from 800 - 2.400 mm optionally available
- Driver's platform possible
- Zinc-plated version on request
- Operating time according to battery capacity



Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
EGU ES 15	1,5 / 1.150	VG / PUR Tandem	*253932
EGU ES 20	2,0 / 1.150	VG / PUR Tandem	*251679
EGU ES 25	2,5 / 1.150	VG / PUR Tandem	*253734
EGU ES 30	3,0 / 1.150	VG / PUR Tandem	*251907

Battery and charger for EGU ES und EGU EK are to be ordered separately - see page 10



Order picking truck Model EGU EK

for order picking and transporting as well as for the deployment of palletised goods on large areas

- Central drive unit with 1,2 kW motor, optional: 1,7 kW
- Hydraulic unit with overload protection by safety valve
- Multifunctional control handle for sensitive operation
- Impulse control for stepless speed regulation
- Longer forks optionally available
- Operating time according to battery capacity

Model	Capacity (t) / Fork length (mm)	Tyres	EAN-No. 4025092*
EKU EK 15	1,5 / 1.150	VG / PUR Tandem	*253949
EKU EK 20	2,0 / 1.150	VG / PUR Tandem	*251686
EKU EK 25	2,5 / 1.150	VG / PUR Tandem	*253956
EKU EK 30	3,0 / 1.150	VG / PUR Tandem	*253963

Drum lifter with quick-lift feature Model FH 300

for the transport of 210 litres (45 gallon) tighthead or open top steel drums with body beads in upright position

- Robust straddle chassis
- Enclosed, low maintenance hydraulic system
- Sensitive lowering of the drum with finely metered lowering speed
- Drum holding clamp with locking device and additional support at the lower drum area for safe transport



Model	Capacity (t) / Lifting height (mm)	Tyres	EAN-No. 4025092*
FH 300	0,3 / 905	PA/PA	*254403

Manual drive stacker/pallet lifter with manual/hydraulic lift Model HV TH

ideal for the occasional, internal application of stacking and transporting of palletised goods

- Ergonomically designed handle incorporating LIFT - NEUTRAL - LOWER functions
- Powerful hydraulic pump and cylinder, providing a quick-lift feature, protected via a pressure relief valve
- Lowering speed can be finely metered for sensitive lowering of the load
- Robust chassis each having two steering wheels and two load rollers; retention is by parking device



Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
HV TH 05-09	0,5 / 1.120 / 900	PUR / PA Single	*254380
HV TH 10-09	1,0 / 1.140 / 900	PUR / PA Single	*254373
HV TH 10-16	1,0 / 1.140 / 1.600	PUR / PA Single	*254397

Manual drive stacker with electro/hydraulic lift Model HV TM

suitable for occasional to medium applications of stacking and transporting palletised loads, also in confined areas

- Easy to operate via tie-rod guides to both steering wheels
- Compact electro/hydraulic lifting device with overload protection and adjustable lowering valve
- Mast welded from precision profiles, fork carriage with maintenance free guide rollers
- Robust chassis with two load rollers and two steering wheels; retention is by a parking device
- Battery and charger are supplied with the unit



Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
HV TM 10-09	1,0 / 1.150 / 900	VG / PA Single	*250610
HV TM 10-16	1,0 / 1.150 / 1.600	VG / PA Single	*250627
HV TM 10-20	1,0 / 1.150 / 2.000	VG / PA Single	*250634
HV TM 12-16	1,2 / 1.150 / 1.600	VG / PUR Single	*252041
HV TM 12-25	1,2 / 1.150 / 2.500	PUR / PA Single	*252423
HV TM 12-29	1,2 / 1.150 / 2.900	PUR / PA Single	*252980
HV TM 12-35	1,2 / 1.150 / 3.500	PUR / PA Single	*253000
HV TM 15-16	1,5 / 1.150 / 1.600	VG / PUR Single	*252034
HV TM 15-25	1,5 / 1.150 / 2.500	VG / PUR Single	*252645
HV TM 15-30	1,5 / 1.150 / 3.000	VG / PUR Single	*252171
HV TM 15-35	1,5 / 1.150 / 3.500	VG / PUR Single	*252249

Higher capacity batteries
see page 10



Electric pedestrian stacker Model EGV TG

ideal for stacking and transportation of palletised goods within a warehouse environment for short haul and medium work load applications

- Reliable impulse control for stepless regulation of drive speed
- Easy to use multi-functional control handle; when the handle is released the brake is automatically applied
- Compact electro/hydraulic lifting device, overload protection and finely metered lowering of load through pressure relief valve and adjustable lowering valve
- Robust frame with one drive wheel, two load and two stabilising rollers
- Battery and battery charger are supplied with the unit

Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
EGV TG 10-16	1,0 / 1.150 / 1.600	PUR+VG / PUR Single	*250672
EGV TG 10-20	1,0 / 1.150 / 2.000	PUR+VG / PUR Single	*250689
EGV TG 12-25	1,2 / 1.150 / 2.500	PUR+VG / PUR Single	*252584
EGV TG 12-29	1,2 / 1.150 / 2.900	PUR+VG / PUR Single	*250719
EGV TG 12-35	1,2 / 1.150 / 3.500	PUR+VG / PUR Single	*252522

Battery and charger have
to be ordered separately,
see page 10



Electric pedestrian stacker Model EGV LE

ideal for stacking and transportation of palletised loads within a warehouse environment for long haul and high work load applications

- Reliable impulse control for stepless regulation of drive speed
- Easy to use multi-functional control handle; when the handle is released the brake is automatically applied
- Compact electro/hydraulic lifting device, overload protection and finely metered lowering of load through pressure relief valve and adjustable lowering valve
- Robust frame with one drive wheel, two load and two stabilising rollers
- Operating time according to battery capacity

Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
EGV LE 12-16	1,2 / 1.150 / 1.600	PUR+VG / PUR Single	*250887
EGV LE 12-25	1,2 / 1.150 / 2.500	PUR+VG / PUR Single	*253512
EGV LE 12-29	1,2 / 1.150 / 2.900	PUR+VG / PUR Single	*250894
EGV LE 12-35	1,2 / 1.150 / 3.500	PUR+VG / PUR Single	*253536
EGV LE 16-16	1,6 / 1.150 / 1.600	PUR+VG / PUR Tandem	*250948
EGV LE 16-25	1,6 / 1.150 / 2.500	PUR+VG / PUR Tandem	*253567
EGV LE 16-29	1,6 / 1.150 / 2.900	PUR+VG / PUR Tandem	*250955
EGV LE 16-35	1,6 / 1.150 / 3.500	PUR+VG / PUR Tandem	*253413
EGV LE 14-45T	1,4 / 1.150 / 4.500	PUR+VG / PUR Tandem	*253819

Electric pedestrian stacker Model EGV LV

ideal for transporting and stacking palletised loads within a warehouse environment for long haul and demanding high work load applications

- Excellent all round vision when manoeuvring and positioning the load due to high visibility mast
- Low overall height and high maximal fork height with TRIPLEX mast
- Reliable impulse control for stepless regulation of drive speed
- Easy to use multi-functional control handle; when the handle is released the brake is automatically applied
- Compact electro/hydraulic lifting device, overload protection and finely metered lowering of load through pressure relief valve and adjustable lowering valve
- Robust frame with one drive wheel, two stabilising wheels and four load rollers
- Operating time according to battery capacity



Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
EGV LV 12-16	1,2 / 1.150 / 1.600	VG+PUR / PUR Tandem	*254137
EGV LV 12-25	1,2 / 1.150 / 2.500	VG+PUR / PUR Tandem	*252805
EGV LV 12-30	1,2 / 1.150 / 3.000	VG+PUR / PUR Tandem	*252706
EGV LV 12-35T	1,2 / 1.150 / 3.500	PUR+PUR / PUR Tandem	*252058
EGV LV 12-40T	1,2 / 1.150 / 4.000	PUR+PUR / PUR Tandem	*253970
EGV LV 12-45T	1,2 / 1.150 / 4.500	PUR+PUR / PUR Tandem	*252546
EGV LV 15-16	1,5 / 1.150 / 1.600	PUR+PUR / PUR Tandem	*253987
EGV LV 15-25	1,5 / 1.150 / 2.500	PUR+PUR / PUR Tandem	*253994
EGV LV 15-30	1,5 / 1.150 / 3.000	PUR+PUR / PUR Tandem	*252485
EGV LV 15-35T	1,5 / 1.150 / 3.500	PUR+PUR / PUR Tandem	*254144
EGV LV 15-40T	1,5 / 1.150 / 4.000	PUR+PUR / PUR Tandem	*251648
EGV LV 15-45T	1,5 / 1.150 / 4.500	PUR+PUR / PUR Tandem	*251952
EGV LV 20-16	2,0 / 1.150 / 1.600	PUR+PUR / PUR Tandem	*253376
EGV LV 20-25	2,0 / 1.150 / 2.500	PUR+PUR / PUR Tandem	*252560
EGV LV 20-30	2,0 / 1.150 / 3.000	PUR+PUR / PUR Tandem	*253628
EGV LV 20-35	2,0 / 1.150 / 3.500	PUR+PUR / PUR Tandem	*252348

Battery and battery charger for models EGV LV und EGI LD have to be ordered separately see page 10

Electric pedestrian stacker with initial lift Model EGI LD

ideal for operation on inclines and ramps within a warehouse environment, for stacking and transporting palletised loads in longer haul and high work load applications

- Reliable impulse control for stepless regulation of drive speed
- Easy to use multi-functional control handle; when the handle is released the brake is automatically applied
- Compact electro/hydraulic lifting device, overload protection and finely metered lowering of load through pressure relief valve and adjustable lowering valve
- Robust frame with one drive wheel, two stabilising wheels and four load rollers
- Operating time according to battery capacity



Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
EGI LD 12-16	1,2 / 1.150 / 1.600	VG+PUR / PUR Tandem	*254007
EGI LD 12-25	1,2 / 1.150 / 2.500	VG+PUR / PUR Tandem	*254014
EGI LD 12-30	1,2 / 1.150 / 3.000	VG+PUR / PUR Tandem	*252324
EGI LD 12-35	1,2 / 1.150 / 3.500	VG+PUR / PUR Tandem	*254021
EGI LD 15-16	1,5 / 1.150 / 1.600	VG+PUR / PUR Tandem	*254038
EGI LD 15-25	1,5 / 1.150 / 2.500	VG+PUR / PUR Tandem	*253338
EGI LD 15-30	1,5 / 1.150 / 3.000	VG+PUR / PUR Tandem	*251808
EGI LD 15-35	1,5 / 1.150 / 3.500	VG+PUR / PUR Tandem	*252744

Battery and charger have to be ordered separately - see below



Electric pedestrian four-way stacker Model EGY LW

ideal for transporting and stacking long goods under demanding conditions

- Takes maximum advantage of available storage space by using four-way technique; load wheels can be hydraulically rotated 90°
- Reliable impulse control for stepless regulation of drive speed
- Easy to use multi-functional control handle; when the handle is released the brake is automatically applied
- Compact electro/hydraulic lifting device, overload protection and finely metered lowering of load through pressure relief valve and adjustable lowering valve
- Robust frame with one drive wheel, two stabilising wheels and four load rollers
- Operating time according to battery capacity

Model	Capacity (t) / Fork length / -height (mm)	Tyres	EAN-No. 4025092*
EGY LW 12-16	1,2 / 950 / 1.600	PUR / PUR Tandem	*254045
EGY LW 12-25	1,2 / 950 / 2.500	PUR / PUR Tandem	*254052
EGY LW 12-30	1,2 / 950 / 3.000	PUR / PUR Tandem	*254069
EGY LW 12-35	1,2 / 950 / 3.500	PUR / PUR Tandem	*254076
EGY LW 15-16	1,5 / 950 / 1.600	PUR / PUR Tandem	*254083
EGY LW 15-25	1,5 / 950 / 2.500	PUR / PUR Tandem	*253772
EGY LW 15-30	1,5 / 950 / 3.000	PUR / PUR Tandem	*254090
EGY LW 15-35	1,5 / 950 / 3.500	PUR / PUR Tandem	*251815

Accessories

Batteries	V / Ah		for truck model	EAN-No. 4025092*
TGB5H	2 x 12 / 125	Traction	EGV TG	*254250
LEB5H	24 / 160	PsZ	EGV LE	*253499
LEB8H	24 / 210	PsZ	EGV LE	*253451
ACB5H	24 / 110	PsZ	EGI LD, EGV LV, EGY LW	*253314
ACB5H-5H	24 / 130	PsZ	EGI LD, EGV LV, EGY LW	*254113
ACB6H	24 / 140	PsZ	EGI LD, EGV LV, EGY LW	*253697
ACB7H	24 / 160	PsZ	EGI LD, EGV LV, EGY LW	*253352
ACB7-5H	24 / 184	PsZ	EGI LD, EGV LV, EGY LW	*253666
ACB8H	24 / 210	PsZ	EGI LD, EGV LV, EGY LW	*251945
ACB9H	24 / 240	PsZ	EGI LD, EGV LV, EGY LW	*252669
ACB10H	24 / 276	PsZ	EGI LD, EGV LV, EGY LW	*252362
ACB5H	24 / 110	PsZ	EGU ES, EKU EK	*252072
ACB5-5H	24 / 130	PsZ	EGU ES, EKU EK	*252409
ACB6H	24 / 140	PsZ	EGU ES, EKU EK	*254106
ACB7H	24 / 160	PsZ	EGU ES, EKU EK	*251914
ACB7-5H	24 / 184	PsZ	EGU ES, EKU EK	*252508
Battery charger			for truck model	EAN-No. 4025092*
C 24-30			all - except EGV TG and HV TM	*251099
Little Mule attachments			for truck model	EAN-No. 4025092*
Driver's platform			EGV LE	*251082
Driver's platform			EGI LD, EGV LV, EGY LW, EGU ES	*251938

Scissor elevating platform, mobile Model HF/S

for lifting and supplying goods independent of the location

- Single scissor construction
- Compact design with low overall height
- Steering and fixed rollers with service-free roller bearings. One steering roller can be locked in position for parking
- Manual hydraulic system with pedal or electro/hydraulic system with deadman function - a mains current connection is not required
- High safety due to pressure relief and lowering valve
- Models with electro/hydraulic pump are supplied complete with battery and charger
- In accordance with EN 1570 and machinery directive 98/37 EC



Scissor elevating platform, mobile Model HF/D

- Same design as model range HF/S, however, with double vertical scissor
- Models with electro/hydraulic pump are supplied complete with battery and charger
- In accordance with EN 1570 and machinery directive 98/37 EC

Model	Capacity (t) / max. / min. Platform height (mm)	Platform dimensions L x W (mm)	EAN-No. 4025092*
HF 015-078 SM	0,15 / 780 / 255	760 x 450	*252867
HF 030-084 SM	0,3 / 840 / 335	840 x 500	*253659
HF 030-084 SE	0,3 / 840 / 335	840 x 500	*253826
HF 050-090 SM	0,5 / 900 / 340	1.030 x 610	*253116
HF 050-090 SE	0,5 / 900 / 340	1.030 x 610	*252881
HF 080-105 SM	0,8 / 1.050 / 360	1.350 x 840	*253475
HF 080-105 SE	0,8 / 1.050 / 360	1.350 x 840	*253239
HF 100-105 SM	1,0 / 1.050 / 360	2.000 x 1.000	*252843
HF 100-105 SE	1,0 / 1.050 / 360	2.000 x 1.000	*253833
HF 125-105 SM	1,25 / 1.050 / 360	1.350 x 840	*252904
HF 125-105 SE	1,25 / 1.050 / 360	1.350 x 840	*253888
HF 012-142 DM	0,125 / 1.420 / 430	840 x 500	*253680
HF 012-142 DE	0,125 / 1.420 / 430	840 x 500	*253840
HF 045-155 DM	0,45 / 1.550 / 295	1.030 x 610	*252928
HF 045-155 DE	0,45 / 1.550 / 295	1.030 x 610	*253857
HF 050-190 DM	0,5 / 1.900 / 490	1.350 x 840	*253437
HF 050-190 DE	0,5 / 1.900 / 490	1.350 x 840	*253864
HF 080-190 DM	0,8 / 1.900 / 490	1.350 x 840	*253758
HF 080-190 DE	0,8 / 1.900 / 490	1.350 x 840	*253871

Elevating work bench, mobile with manual or electro/hydraulic lift Model HT

the elevating work bench is used in manufacturing and assembly processes for positioning and lifting tools or other heavy loads

- Sturdy frame with two trestle and two steering rollers; retention is by a parking device on the steering roller.
- Large stroke for every pump action by hydraulic unit with double-acting hand pump protected by a pressure relief valve
- Battery and charger - where applicable - are supplied with the unit



Model	Capacity (t) / max. / min. Platform height (mm)	Platform dimensions L x W (mm)	EAN-No. 4025092*
HT 08 M	0,8 / 1.450 / 690	800 x 750	*251990
HT 08 E	0,8 / 1.450 / 690	800 x 750	*252003

Your Little Mule® Dealer:

Yale Industrial Products GmbH

P. O. Box 10 13 24 · D-42513 Velbert · Phone 00 49 (0) 20 51/600-0 · Telefax 00 49 (0) 20 51/600-194 · e-mail: info@little-mule.com